



- Bonded Junction Maximum temperature – PVC 100°C
- Bonded Junction Maximum temperature – Teflon 240°C
- Bonded Junction Maximum temperature – Fibreglass 300°C

- Insulated Junction Maximum temperature – PVC (waterproof) 100°C
- Insulated Junction Maximum temperature – Teflon (waterproof) 240°C
- Insulated Junction Maximum temperature – Ceramic Bead Fibreglass 300°C

- TYPE K THERMOCOUPLE
- TYPE J THERMOCOUPLE
- TYPE T THERMOCOUPLE
- TYPE N THERMOCOUPLE

**THERMOCOUPLE
NO POT
TC02 STYLE**

TEMPERATURE CONTROLS PTY LTD Certificate No: QEC 14412
ISO 9001:2008

CONDITIONS

THIS DRAWING IS OUR EXCLUSIVE PROPERTY AND MUST NOT BE COPIED OR HANDED TO ANY OTHER PARTIES WITH OUT WRITTEN PERMISSION. IT SHALL BE RETURNED UPON REQUEST

SYDNEY : 7 YAMMA ST SEFTON , NSW 2162
PHONE : (02) 9721 8644 FAX : (02) 9738 9339
MELBOURNE : 8/280 Whitehall St
YARRAVILLE VIC 3013
PHONE : (03) 9687 0000 FAX : (03) 9687 1900
EMAIL : sales@temperature.com.au



TITLE

SIZE : A4	DATE :20/04/09	DWG NO : SD 359
SCALE : NTS	DRAWING BY K.F	REV : 01