



2mm THICK
 HOLES ARE 9.5mm DIA,
 10.25mm FROM BOTTOM AND TOP EDGES
 = CENTRE OF HOLE
 8.25mm FROM SIDE EDGE
 = CENTRE OF HOLE



- TYPE K THERMOCOUPLE
- TYPE N THERMOCOUPLE
- TYPE J THERMOCOUPLE
- TYPE T THERMOCOUPLE
- RTD PT100

C\W STAINLESS STEEL L BRACKET

OPTION - Ex ia
 Compliance with ANSI AS/NZS 60079. 11.2006 Explosive Atmospheres,
 Intrinsic safety Ex ia (1047 RTD & TC)

TEMPERATURE CONTROLS PTY LTD Certificate No: QEC 14412
 ISO 9001

CONDITIONS
 THIS DRAWING IS OUR EXCLUSIVE PROPERTY AND MUST NOT BE COPIED OR HANDED TO ANY OTHER PARTIES WITH OUT WRITTEN PERMISSION. IT SHALL BE RETURNED UPON REQUEST

SYDNEY : 7 YAMMA ST SEFTON , NSW 2162
 PHONE : (02) 9721 8644 FAX : (02) 9738 9339
 MELBOURNE : 8/280 Whitehall St
 YARRAVILLE VIC 3013
 PHONE : (03) 9687 0000 FAX : (03) 9687 1900
 EMAIL : sales@temperature.com.au



TITLE		
SIZE : A4	DATE : 23/06/11	DWG NO : SD 855
SCALE : NTS	DRAWING BY R.B	REV: 01