



**NOTE: Standard taper length up to 400mm
for longer taper lengths or full taper refer to SD 036FT**

SPECIFICATION	D2	D1	AF HEX	E	F	U
1/2" NPT / BSP	16mm	12mm	25.4mm	23mm	45mm	SPECIFY
3/4" NPT / BSP	19mm	16mm	28.5mm	23mm	45mm	SPECIFY
1" NPT / BSP	22mm	19mm	34.8mm	25mm	50mm	SPECIFY

316 STAINLESS STEEL BAR STOCK TAPER THERMOWELL

Specify	Quality assurances Documentation	Certificate Reference
	Material certificate – barstock	ORIGINAL
	Hydrostatic Pressure test certificate - Internal	1044
	NACE - Heat treatment certificate	1045
	Cleaned for oxygen IEC 60877 Sealed in plastic bag	1055
	Thermowell calculation to ASME PTC 19.3	1135
	Tagging	STAMP
	ITP (specify)	1056 C
	Other	Specify

TEMPERATURE CONTROLS PTY LTD Certificate No: QEC 14412
AS/NZS 9001:2000

CONDITIONS

THIS DRAWING IS OUR EXCLUSIVE PROPERTY AND MUST NOT BE COPIED OR HANDED TO ANY OTHER PARTIES WITH OUT WRITTEN PERMISSION. IT SHALL BE RETURNED UPON REQUEST

SYDNEY : 7 YAMMA ST SEFTON , NSW 2162
PHONE : (02) 9721 8644 FAX : (02) 9738 9339
MELBOURNE : 8/280 Whitehall St
YARRAVILLE VIC 3013
PHONE : (03) 9687 0000 FAX : (03) 9687 1900
EMAIL : sales@temperature.com.au



TITLE

SIZE : A4	DATE : 10/09/09	DWG NO : SD 036
SCALE : NTS	DRAWING BY K.F	REV : 04